
Fasenfräser, 15°, 30°, 45°, 60° und 75°

									format professional spality	
K	\emptyset D ₁	$ØD_2$	\emptyset d H7	Н		Anzahl	a _p max.		2999	Bestell-
0	mm	mm	mm	mm	zc*	WSP	mm	Wendeschneidplatte	€	Nr.
15	35	94	27	50	3	6	8	XPHT 1604	536,00	0723
30	35	88	27	50	3	6	15	XPHT 1604	536,00	0726
45	35	77,8	27	50	3	6	21,5	XPHT 1604	536,00	0729
60	35	65	27	50	3	6	26,5	XPHT 1604	536,00	0732
75	35	50,7	22	60	3	6	29,5	XPHT 1604	536,00	0735
* Effektive Zähnezahl für Vorschubberechnung.									(W280)	





Ersatzteil

		format	M Wera	
	VE	2999	5886	Bestell-
Ausführung		€	€	Nr.
Schraube	5 Δ	6,25	-	0744
Schraubendreher, T15 x 80 mm	1	_	6,90	0050
Δ Abgabe nur als ganze Verpackungseinheit möglich.		(W281)	(W543)	



ISO-Wendeschneidplatte





										professional quality	
		Schnittgeschw.								2999	Bestell-
		Vorschub	Р	M	K	N	S	Н	VE		Nr.
ISO-Bezeichnung	Schneidstoffsorte	Schnitttiefe	Stahl	Rostfrei	Guss	Alu	Superleg.	Hart		€	
XPHT 160412S	PM 9125	v _c m/min	150-215	90-130	-	-	30-75	-	10 Δ	19,10	5551
	M 8	f_z mm	0,1-0,3	0,1-0,23	-	-	0,1-0,18	-			
		a _p mm	1,2-15	1,2-11,3	-	-	1,2-9	-			
XPHT 160412S	PM 9130	v₀ m/min	160-255	95-150	-	-	-	-	10 Δ	19,00	5548
	₽	f_z mm	0,1-0,3	0,1-0,23	-	-	-	-			
		a _p mm	1,2-15	1,2-11,3	_	_	-	-			

